

PERFORMA SYNTHETIC

SAE 5W-30

Product Description

PERFORMA SYNTHETIC is premium fully synthetic motor oil with medium ash formulation that provides high performance engine protection for superior performance vehicles including European diesel passenger cars up to Euro 6 emission standard. The motor oil is compatible with after treatment device such as Diesel Particulate Filter (DPF), allows a smooth acceleration response, greater fuel economy, engine cleansing and sludge protection.

Benefits

- High thermal stability and oxidation resistance for excellent protection against sludge and filter blocking
- Superior deposit control that actively keep engine clean
- Better lubrication and wear protection when start-up and even under severe conditions
- Enhanced acceleration booster for maximum accelerating performance
- Fuel economy performance and seal compatibility
- Extends oil drain interval
- Prolongs the service life of catalytic converter

Applications

- Designed for use in superior performance vehicles including European diesel passenger cars up to Euro 6 emission standard
- Recommended for vehicles using gasoline and ethanol blends: E10, E20 and E85
- Applicable for gas engines: CNG and LPG

The Moving Innovation 

PERFORMA SYNTHETIC

SAE 5W-30

Typical Characteristics

Test	Methods	Units	Results
			5W-30
Density at 15 °C	ASTM D4052	g/cm ³	0.85
Kinematic Viscosity at 40 °C	ASTM D445	mm ² /s	54.0
Kinematic Viscosity at 100 °C	ASTM D445	mm ² /s	10.1
Viscosity Index	ASTM D2270		178
Cold-Cranking Simulator at -35 °C	ASTM D5293	mPa.s	6,000
MRV at -40 °C	ASTM D4684	mPa.s	26,000
Flash Point (COC)	ASTM D92	°C	220
Pour Point	ASTM D5950	°C	-45

Performance Standard

- API SN/CF
- ACEA A5/B5/C2

Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from <http://pttlubricants.pttplc.com>

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTT Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTT Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.